



129.00 EUR

incl. 19% VAT, plus [shipping](#)

- Fanless !
- 1.6Ghz !
- FSB800 !



- VIA VX800 Chipset
- VIA Eden 1.6GHz(90nm,FSB 800MHz,1.6GHz) processor
- Integrated Chrome9 HC3 DX9 IGP
- Integrated LVDS support 24-bit TFT LCD
- Support 1 x 32-bit PCI slot
- Support 2 x Serial ATA 2 Devices
- Windows Vista Ready
- Onboard Gigabit LAN
- Support DC Fan
- VIA VT1708B HD Audio Codec with 6-Channel
- 170 x 170mm Mini-ITX Form Factor
- Support Watch dog Technology

CPU	Support VIA Eden 1.6GHz(90nm,FSB 800MHz, 1.6GHz) processor Front Side Bus 800MHz
Chipset	VIA VX800 Chipsets VIA Chrome9 HC3 IGP, 128Bit 3D engines(Share System Memory:64/128/256MB)
Memory	1 * 240-pin DIMM Sockets for un-buffered DDR2 667MHz SDRAM up to 2GB
Expansion Slots	1 * 32-bit PCI slots
Power Management	ACPI S3/S4 Compliant ,supports VIA PowerSaver™ feature
Storage	2 * Serial ATA2 3Gb/s connectors with RAID 0,1 functions 1 * 40-PIN Ultra DMA 133/100/66 IDE connector
Audio	VIA VT1708B HD Audio Codec with 6-Channel
Ethernet LAN	1 * RTL8111C 10 / 100 / 1000 PCI LAN
USB	Embedded 4 * USB 2.0/1.1

LVDS	Onboard 24-bit dual channel LVDS connector 4 * USB 2.0/1.1 ports 1 * PS/2 connector for Keyboard and Mouse 1 * RJ-45 ports
Rear Panel I / O	3 * Audio I/O ports (Line-in, mic and line-out) 1 * VGA port 1 * DB-9 RS232 COM port 1 * DB-25 Connector for Printer Port 1 * CPU Smart Fan Connector, 2 * Sys/Chassis Fan Connectors 3 * 9-Pin COM Port headers
Internal I / O	1 * WI-FI header 1 * LVDS header 1 * IR header
BIOS	Award 4MB DIP-SPI Flash ROM
Form Factor	Mini-ITX (170mmx170mm)
Temperature	Operating within 0~60 centigrade Storage within -20-85 centigrade

Scope of supply:

- Jetway JNF77-1G6E-LF with 1.6Ghz CPU
- DriverCD
- Manual
- ATX shield
- IDE-cable
- SATA-cable