



249.00 EUR
incl. 19% VAT, plus [shipping](#)

- 2x Gigabit LAN !
- Metal enclosure !
- VESA Mount !
- WLAN/BT !

- Intel® Celeron® processor N3060
- 2 x SO-DIMM DDR3L slots
- 2 x GbE LAN ports (Realtek RTL8111HS)
- 8GB onboard eMMC memory
- 1 x Full-size Mini-PCIe slot for 3G module or mSATA storage
- 1 x SDXC card slot
- Supports Windows 7/ 8.1/ 10 and Android 5.1

Intel® Celeron® processor N3060

2 cores, 2 threads

1.6 - 2.48 GHz

2MB L2 cache

6W max. TDP

2 x SO-DIMM slots

1.35V DDR3L memory

Up to 8GB

1333/1600MHz

8GB eMMC

CPU

Memory

Flash Memory

LAN	2x GbE LAN ports (Realtek RTL8111HS)
Video	Intel HD Graphics supports dual display
	Max. resolution via HDMI ports: 3840 x 2160 @ 30Hz or 2560 x 1600 @ 60Hz with 2 memory installed
Audio	Max. resolution via eDP: 2560 x 1440 @ 60Hz with 2 memory installed
	Realtek ALC255 controller Supports 2/4/5.1/7.1 channel configurations via HDMI 1 x Full-size Mini-PCIe slot (for 3G module or mSATA storage) 1 x Half-size Mini-PCIe slot (for pre-installed WiFi+BT module) 1x TPM Pin header
Expansion	<i>Pre-installed:</i> - 1 x WiFi + Bluetooth card
	- Intel Dual Band Wireless-AC 3160 - Supports IEEE 802.11b/g/n/ac - Supports Bluetooth 4.0 - Bluetooth function does not support under Windows 7 embedded OS
Rear I/O	1x DC-in 2x HDMI v1.4b 2x RJ45
	Windows 10 64bit Windows 8.1 64bit Windows 7 32bit / 64bit
OS Compability	Ubuntu 15.10 Ubuntu 16.04 LTS Android 5.1
	AC 100~240V 19V DC-in 65W/3.42A
Power supply	1x SDXC card slot 4x USB 3.0 1x SDXC card slot
	1x Headphone-out / MIC-in 1x Power button with LED 1x HDD activity LED 3x LEDs reserved for user configuration
Storage	MZBSWFP 140.8 x 107.5 x 27 mm 560g
	1x Micro-B USB 2.0
Front I/O	1x Micro-B 5-pin *RS232 full-duplex port (TxD, RxD, CTS, RTS, GND) 1x Kensington Lock
	Operating temperature: 0°C to 40°C Operating humidity: 0%-90% (non-condensing) Non-operating temperature: -20°C to 60°C Non-operating humidity: 0%-95% (non-condensing)
Motherboard	
Dimensions	
Weight	
Side I/O	
Operating Properties	