



569.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake-UP3 !
- 3x USB-C !
- 2x LAN !
- NUC Fromat !

- Intel® 11th Gen. Tiger Lake-UP3 SoC Processor
- 2* DDR4 3200MHz SO-DIMM up to 64GB
- Rich and complete connection interface
- supports 4 sets of 4K HDR output
- 3* internal M.2 expansion slots for various applications

Model	– N11-1115 (CPU : 1115G4) – N11-1135 (CPU : 1135G7)
CPU/Chipset	– Intel® Tiger Lake-UP3 Processor
BIOS	– AMI Flash ROM
Memory	– 2* DDR4 3200MHz up to 64GB
Network	– 1* Intel i219-LM GbE – 1* Intel i225-V 2.5GbE
Graphics	– Intel® UHD / Iris Xe Graphics, shared memory – 2* HDMI 2.0b (Max Resolution: 4096x2160@60Hz) – 2* DP1.4 (Max Resolution: 4096x2304@60Hz) from Type-C – Support Four independent 4K HDR Displays
Storage	– 1* M.2 M-key 2242/2280 (PCIe4.0 x4/SATAIII interface) support NVMe – 1* 2.5" SATA Device (support 2.5" HDD with a height ≤ 10mm)
Expansion slot	– 1* M.2 E Key 2230 for WiFi module – 1* M.2 B Key 3042/3052 for 4G/5G module

Rear Panel I/O	<ul style="list-style-type: none"> - 2* USB3.2 (Gen.2) Type-C support DP1.4 display output - 1* SIM Card slot - 2* HDMI 2.0 - 2* RJ45 - 1* DC Jack
Front Panel I/O	<ul style="list-style-type: none"> - 1* Audio (Line out +MIC combo) - 2* USB3.2 / A type (Gen.2) - 1* USB3.2 / C type (Gen.2) - 1* Power Button - 1* Power LED
Internal Connector	<ul style="list-style-type: none"> - 1* SATAIII - 1* AT/ATX mode jumper - Onboard TPM2.0 (option)
Compliance	- CE, FCC, RoHS, ErP Ready
Power Source	<ul style="list-style-type: none"> - MB : DC12~24V input - Adapter : DC12V_90W
Compliance	- CE, FCC, LVD, RoHS
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -10 ~ 50° C - Storage Temperature: -20 ~ 60° C
Dimensions	<ul style="list-style-type: none"> - System: 121 (W) x 113.4 (D) x 59 (H) mm - Box: 244 (W) x 183 (D) x 118 (H) mm
OS Support	- Windows 11, Linux